

Combi steamer

FlexiCombi®

Electric combi steamer FlexiCombi® Classic 6.1

MKN-No.: FKECOD615CG2



world of cooking

FKECOD615CG2

Features

- Analogue setting and digital display for cooking temperature, humidity, cooking time and core temperature
- **Manual operation concept** with 6 cooking modes: SoftSteaming, Steaming, ExpressSteaming, Convection, CombiSteaming and Regeneration
- 100 cooking programmes can be saved
- Cooking Steps function – up to 6 programme steps can be individually combined
- **FlexiRack®** – capacity concept for an increase in capacity over 50% *
- **EasyLoad – crosswise insertion supplied as standard** for increased occupational safety
- **DynaSteam** – dynamic process-oriented steam quantity adjustment depending on product load
- Dynamic autoreverse fan for extremely uniform cooking results
- 5 fan speeds programmable
- Fan safety brake
- Integrated grease separation system
- **Hygienic cooking chamber door with sealed triple glazing**
- Right hand hinged door
- LED lighting integrated into the hygienic cooking chamber door
- **Hygienic cooking chamber** of corrosion resistant stainless steel
- **ClimaSelect®** – Climate control in steps of 25 %
- **Ready2Cook** – preheating, cooling down, climate preparation
- Internal core temperature measurement (up to 99 °C)

Accessories

- Hanging rack for crosswise insertion, standard configuration, 6 shelf inserts for GN 1/1 and FlexiRack®, with tilt protection for containers, distance between insert levels 68 mm



Option

- Mains connection cable with 5-channel CEE plug
- Mains connection cable without CEE plug
- **WaveClean®** – automatic cleaning system, siphon is included with the appliance
- **Integrated shower hose**
- Left hand hinged door
- Two position safety door lock
- Internal multipoint core temperature probe
- Additional external multi-point core temperature probe (can not be retrofitted; can be used at the same time as an internal multipoint core temperature probe)
- Additional external sous vide single point sensor (can not be retrofitted)
- IPX 6 – Protection against strong jets of water
- Marine version
- USPH version on request
- Prison version
- Special voltage
- Interface for connection to an energy optimization system according to DIN 18875 and potential free contact
- MKN SteelPlus – CO₂e-reduced stainless steel (Scope 1, 2, 3)***

Product safety



* compared to GN 1/1

*** Further information at: www.mkn.com/en/sustainability/mkn-steelplus

Combi steamer
FlexiCombi®
 Electric combi steamer FlexiCombi® Classic 6.1
 MKN-No.: FKECOD615CG2



world of cooking

FKECOD615CG2

Capacity	
Shelf inserts	6
GN 1/1 (530 x 325 x 65 mm)	6
Baking standard (600 x 400 x 85 mm)	5
FlexiRack® (530 x 570 x 65 mm)	6 (≈ 10x GN 1/1)
Plates (Ø 28 cm on FlexiRack® grids)	24
Plates (Ø 32 cm – plate rack trolley)	22
Meals per day	30 - 100 (GN 1/1); 30 - 150 (FlexiRack®)

Electricity supply (380 V)	
Nominal power consumption (kW)	9.4
Voltage (V)	380 3 (N)PE AC
Fuse protection (A)	3 x 16
Frequency range (Hz)	50 / 60

Electricity supply (400 V)	
Nominal power consumption (kW)	10.4
Voltage (V)	400 3 (N)PE AC
Fuse protection (A)	3 x 16
Frequency range (Hz)	50 / 60

Electricity supply (415 V)	
Nominal power consumption (kW)	11.2
Voltage (V)	415 3 (N)PE AC
Fuse protection (A)	3 x 16
Frequency range (Hz)	50 / 60

Electricity supply (440 V)	
Nominal power consumption (kW)	10.4
Voltage (V)	440 3 (N)PE AC
Fuse protection (A)	3 x 16
Frequency range (Hz)	50 / 60

Drinking water cold (KW/TWk)	
Water pressure (bar)	2 - 6
Connection size	DN 20 (G ¾" A)
Quality mmol/l	< 4
Consumption cleaning (l)	32

Soft water (EW/EWk)	
Water pressure (bar)	2 - 6
Connection size	DN 20 (G ¾" A)
Quality mmol/l	< 0.9
Consumption steaming (l/h)	16
Consumption combisteaming (l/h)	3.5
Consumption cleaning (l)	3

Waste water (A/A)	
Volume flow max. (l/min)	10
Connection size	DN 50
Quality	max. 80 °C

According to VDI 2052 with a connection voltage of 400 V.	
Operated without steam condensate hood	
Heat emission latent (W)	1872
Heat emission sensitive (W)	1248
Steam output (g/h)	2756
Operated with FlexiCombi® Air condensation hood	
Heat emission latent (W)	562
Heat emission sensitive (W)	1248
Steam output (g/h)	827
Noise level (db (A))	< 70
Type of protection	IPX5



Further features

- One hand door handle
- Non-contact door switch, door lock positions with end stop
- Insertable door seal – end user replaceable
- Drip pan with permanent drainage
- Manual cleaning programme (does not apply to WaveClean® option)
- Energy supply as required
- Reduced heat output (E/2)
- **Integrated heat exchanger**
- HACCP basic version
- Timer with start time pre-selection
- Manual steam injection/humidification
- USB interface, e.g. for software updates**
- Loudspeaker, adjustable tone control
- Audible signal after cooking time has elapsed
- Potential free contact for external steam condensate hood
- Direct waste water connection according to DVGW is possible

Special equipment

216232	Cabinet frame open on all sides (1000 x 655 x 850 mm)
216251	Cabinet closed on three sides (1000 x 696 x 850 mm)
FKE_AIR_6_10	FlexiCombi® Air condensation hood
FKE_AIR_KIT_TEAM	FlexiCombi® Air condensation hood for electric stacking kits
845906	Stacking kit for electric table top appliances (6.x + 10.x / 6.x + 6.x)
216243	Cabinet frame open on all sides, 270 mm high (6.x + 6.x)

FlexiRack® trays (please refer to accessories brochure)

206050	Frying basket
202363	Granite enamelled tray, 20 mm deep
202368	Baking tray – perforated
206045	Grid
10017446	Chicken grill rack

GN 1/1 trays (please refer to accessories brochure)

10012901	Frying basket
202345	Granite enamelled tray, 20 mm deep
202379	Baking tray – perforated
206104	Grid
202375	Cup baking tray (11 cups)

e.g. Starter, baking, GN packages available!

216261	Plate rack
216262	Roll-in rack for GN 1/1 crosswise insertion
216264	Transport trolley rack, 850 mm high
850256	Roll-in frame for transport trolley rack
201790	Thermal insulation cover

TWO_IN_ONE	WaveClean two-in-one cleaning cartridge
------------	---

813636	GN insert lengthwise
845946	Hanging racks baking tray size
10033657	Heat shield left

** without surcharge under <https://shop.mkn.de>

